



BF SERIES WAFER/LUG INDUSTRIAL BUTTERFLY VALVE

Suggested Specifications

GENERAL

Valve shall be capable of bi-directional, drop tight service to 230 psi for 2"-12" size valves and 150 psi for 14"-48" valves, when installed between flanges. Valves shall be Pratt Industrial BF Series Wafer/Lug Industrial Butterfly Valve as manufactured by us.

FLANGE MATING

Valve body shall be ductile iron to mate between ANSI B16.1, Class 125 flanges. Valve neck length shall be sufficient to allow for flange clearance and piping insulation. Flange gaskets shall not be required.

VALVE SEATS

A tongue and groove EPDM, Buna-N or Viton seat shall ensure drop-tight, bi-directional shutoff and shall be field replaceable. The seat shall fully isolate the valve body, stem and journal areas from the flowing media. For air service the EPDM seat shall be rated for 250 degree operating temperature at 15 psi.

VALVE DISC

Based on application valve disc shall be Ductile Iron/Nickel Plated or Nylon-11 coated, CF8M Stainless Steel or Aluminum Bronze with edges and hubs hand polished to a 32 AARH or better finish.

VALVE STEM

The stem shall be two-piece stainless steel.

PACKING

Valves shall be provided with bi-directional stem packing.

For more information about Pratt or to view our full line of water products, please visit www.prattvalve.com or call Pratt customer service at 1.800.423.1323.

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Mi.Net®, Milliken®, Pratt®, Singer®, and U.S. Pipe Valve & Hydrant. Please see www.muellerwp.com/about to learn more.

Copyright © 2018 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).