

# LVC CYLINDER OPTIONS SERIES "VE" KNIFE GATE VALVES

# **FEATURES**

The following are available on all "VE" series cylinders:

#### **Repair Kits**

Kit includes cups and seals to repair worn components. It is recommended that at least one repair kit be kept on hand for each cylinder size.

# Stainless Steel (SS) Rod

17-4PH stainless steel rod should be used in environments where pitting of the cylinder rod may occur. Pitting of the cylinder rod could lead to premature rod seal failure.

#### **Viton Seals**

Used on cylinders exposed to high temperatures. Recommended on any cylinder that will reach operating temperatures of 200°F or higher.

## **Internal Plating**

For use with water or when operating air contains moisture.





### **CYLINDER SIZING CHART**

		CYLINDER SIZING CHART  Maximum Pressure Differential Across Gate											
Valve	Cylinder												
	Pressure ( PSI)	Up to 25 PSI CYL SIZE		25-50 PSI CYL SIZE		50-75 PSI CYL SIZE		75-100 PSI CYL SIZE		100-125 PSI CYL SIZE		125-150 PSI CYL SIZE	
Size	(15)		93					53,65,77		53,65,77			93
	40	53,65,77	93	53,65,77 6	93 4	53,65,77	93 4	6	93 5		93 5	53,65,77 6	5
3	60	6 5	3.25	5	3.25	6 5	3.25	5	4	6 5	4	5	4
	80	4	2.5	4	3.25	4	3.25	4	3.25	4	3.25	4	3.25
	100	4	2.5	4	2.5	4	2.5	4	2.5	4	2.5	4	2.5
4			4					7					
	40	6		6	5	6	5		5	7	6	7	6
	60 80	5 4	3.25 2.5	5 4	4 3.25	5 5	4 4	6 5	5 4	6 5	5 4	6	5 4
	100	4	2.5	4	3.25	5	3.25	5	3.25	5	4	5	4
6	40	7	5	7	6	8	6	8	7	8	7	10	8
	60	6	4	6	5	7	5	7	6	7	7	8	7
	80	6	4	6	4	6	4	6	5	7	5	7	6
	100	5	3.25	5	4	6	4	6	5	6	5	7	5
	40	8	6	8	7	8	7	10	8	12	10	12	10
8	60	7	5	7	6	7	6	8	7	10	8	10	8
	80	6	4	6	5	6	5	7	6	8	7	8	7
	100	6	4	6	5	6	5	7	6	7	6	7	6
10	40	10	7	10	8	12	10	12	10	14	12	14	12
	60	8	6	8	7	8	7	10	8	12	10	12	10
	80	7	5	7	6	7	6	8	7	10	8	12	8
	100	7	5	7	6	7	6	8	7	8	7	10	8
12	40	12	8	12	10	12	10	14	12	16	14	16	14
	60		6	10	7	10	8	12	10	14	12	14	
	80	10 8	6	8	7	10	7	10	8	12	10	12	12 10
	100	8	5	8	6	8	7	10	8	10	8	12	10
	40	12	10	12	12	14	12	16	14	18	16	18	16
14	60	12	7	12	10	12	10	14	12	14	12	16	14
	80	10	7	10	8	10	8	12	10	12	10	14	12
	100	8	6	8	7	10	8	10	10	12	10	12	10
16	40	14	10	14	12	16	14	18	16	20	16	20	18
	60	12	8	12	10	14	12	14	12	16	14	18	14
	80	10	7	10	8	12	10	14	12	14	12	16	14
	100	8	7	10	8	10	10	12	10	12	12	14	12
18	40	14	12	16	14	18	16	20	18	22	20	22	22
	60	12	10	14	12	14	14	16	14	18	16	18	18
	80	10	8	12	10	14	12	14	12	16	14	16	16
	100	10	8	10	10	12	10	12	12	14	12	14	14
20													
	40	16	12	18	16 12	20	18	22	20	22	22	24	24
	60	12	10	14	12	16	14	18	16	20	18	20	20
	80	10 10	10 8	12 12	12 10	14	12 12	16	14	16	16	18	16
	100					12		14	12	16	14	16	14
24	40	16	14	20	18	22	20	24	24	*	*	*	*
	60	14	12	16	14	18	18	20	20	22	20	24	22
	80	12	10	14	12	16	14	18	16	20	18	20	20
	100	12	10	12	12	14	14	16	14	18	16	18	18

<sup>\*</sup> Consult Factory

Mueller refers to one or more of Mueller Water Products, Inc. a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller", Echologics", Hydro-Guard", HYMAX\*, i2O\*, Jones®, Krausz®, Mi.Net®, Milliken\*, Pratt\*, Pratt Industrial\*, Sentryx™, Singer\*, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands and krauszusa.com to learn more.

Copyright © 2025 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).

