

GLOBE STYLE CHECK VALVE

Check valve shall be of the silent operating type and the same size as the entering pipe.

Globe style thru 24 inches shall be rated 250PSI WOG, have a Ductile Iron body (ASTM A-536 65-45-12), 125# ANSI Flat Face Flanges, ASTM Type 316 Stainless Steel helical or conical spring, ASTM 304 Stainless steel valve seat with integral EPDM seat seal, ASTM Type 304 dual guided disc (top and bottom), 304 Stainless Steel guide bushing and type 304 Stainless Steel guide pins.

Check valve to have a minimum open area in the body of 110% of the area of the entering or corresponding pipe.

Valve is to operate silently in either vertical or horizontal positions, flow up or down.

Globe Style Check Valve shall be Pratt Series 821A as manufactured by the Henry Pratt Company.



Henry Pratt Company 1.630.844.4000
www.henrypratt.com
moreinfo@henrypratt.com

Mueller Canada) 1.905.878.0541
www.muellercanada.com
more-info@muellercanada.com

International 1.423.490.9555
www.mueller-international.com
international@muellercompany.com

Copyright © 2016 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document herein are the property of Henry Pratt Company, its affiliates or other third parties.