

SUGGESTED SPECIFICATIONS

PRATT®

WAFER SILENT CHECK VALVE

Check valve shall be of the silent wafer type and the same size as the entering pipe.

Valves shall be the compact wafer style and have a pressure and temperature rating equal to or greater than the pipeline in which they are installed. Compact wafer-silent style check valves thru 12 inches shall be rated for 250PSI WOG for installation between ANSI Class 125 or Class 250 flanges, have a Ductile Iron body (ASTM A-536 65-45-12), ASTM Type 316 Stainless Steel helical or conical spring, ASTM 304 Stainless Steel valve seat with integral EPDM seat seal, ASTM Type 304 Stainless Steel dual guided disc (top and bottom), Bronze (ASTM B584) guide bushing and type 304 Stainless Steel stem.

Valves are to operate silently in either vertical or horizontal positions, flow up or down.

Compact wafer-silent check valve shall be Pratt Series 720G as manufactured by the Henry Pratt Company.



Henry Pratt Company 1.630.844.4000
www.henrypratt.com
moreinfo@henrypratt.com

Mueller Canada 1.705.719.9965
www.muellercanada.com
more-info@muellercanada.com

International 1.423.490.9555
www.mueller-international.com
international@muellercompany.com

Copyright © 2016 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document herein are the property of Henry Pratt Company, its affiliates or other third parties.