




584	End Plate D	Bronze	B 62 Alloy C83600	1
583	End Plate C	Ductile Iron	A 536 Gr. 65-45-12	1
430	Hinge Pin B	Stainless Steel	A 276 Type 304	1
384	Pin	Stainless Steel	A 276 Type 304	2
355	Body O-Ring	Rubber (Buna N)	D 2000 BK 707	1
354	Disc O-Ring	Rubber (Buna N)	D 2000 BK 707	1
353	O-Ring D	Rubber (Buna N)	D 2000 BK 707	1
352	O-Ring C	Rubber (Buna N)	D 2000 BK 707	2
351	O-Ring B	Rubber (Buna N)	D 2000 BK 707	2
325	Gasket C, D	Non Asbestos Sheet	_____	1
324	Gasket A, B	Non Asbestos Sheet	_____	2
234	Socket Head Bolt	Stainless Steel	A 276 Type 304	1 set
210	Eye Bolt	Galvanized Steel	_____	1
198	End Plate Bolt A, B	Zinc Coated Steel	A 307 Grade B	2 set
161	Key	Stainless Steel	A 276 Type 304	2
159	Hinge Pin A	Stainless Steel	A 276 Type 304	1
153	Body Bolt	Zinc Coated Steel	A 307 Grade B	1 set
140	End Plate Bolt C, D	Zinc Coated Steel	A 307 Grade B	2 set
062	Disc Seat Ring	Stainless Steel	A 276 Type 304	1
061	Body Seat Ring	Stainless Steel	A 276 Type 304	1
057	End Plate (B)	Ductile Iron	A 536 Gr. 65-45-12	1
047	Body B.	Ductile Iron	A 536 Gr. 65-45-12	1
020	Sleeve	Bronze	B 62 Alloy C83600	2
015	End Plate (A)	Ductile Iron	A 536 Gr. 65-45-12	1
003	Disc	Ductile Iron	A 536 Gr. 65-45-12	1
001	Body A.	Ductile Iron	A 536 Gr. 65-45-12	1
NO.	PARTS	MATERIAL	ASTM. DESIGN.	Q' TY

MATERIAL LIST

HYDRO	SHELL	500	PSI.
HYDRO	VALVE SEAT	250	PSI.
HYDRO	BACK SEAT	—	PSI.
AIR	SEAT	—	PSI.
STEAM		—	PSI.

TEST PRESSURE

WORKING PRESSURE	250	PSI.
------------------	-----	------

PRATT
a MUELLER brand

TOLERANCES UNLESS OTHERWISE NOTED 4 PLACE DEC. ±.0005 3 PLACE DEC. ±.005 2 PLACE DEC. ±.01 FRACTIONAL ±1/64 ANGULAR ±1/2° MACH. FIN. 63 ✓ BREAK SHARP .015 EDGES MAX.	SCALE N.T.S.	DR. TT CHK. AM APP.	DATE 12/18/19 E.C.N.	REF. DWG. USA1466E
	TITLE TILTED DISC CHECK VALVE SIZE 14"–48" EXPLODED VIEW			
	MODEL	DWG. NO. GA–12554		REV. 0