



Working
 18
 CCNE
 150 PSI
 AWMA C508
 CI
 SERIES 8000
 200-
 CI

Remark - Flanged dimensions follow ANSI B16.1 CL.125

NO.	PARTS	MATERIAL	ASTM DESIGNATION	QTY
462	Retaining Plug	Brass	B 21	1
351	D-Ring	Rubber (Buna N)	D 2000 BK 707	2
327	Gasket	Rubber (Buna N)	D 2000 BK 807	2
324	Cover Gasket	Rubber (Buna N)	D 2000 BK 807	1
262	Disc Bolt	Stainless Steel	A 276 Type 304	1
199	Seat Holder Bolt	Stainless Steel	A 276 Type 304	1set
197	Weight Bolt	Zinc Coated Steel	A 307 Grade B	2
194	Cover Bolt & Nut	Zinc Coated Steel	A 307 Grade B	1set
166	Plug 1/2"	Malleable Iron	A 47	1
161	Key	Stainless Steel	A 276 Type 304	1
159	Hinge Pin	Stainless Steel	A 276 Type 304	1
155	Weight Arm	Ductile Iron	A 536 Gr. 65-45-12	1
088	Seat Nut	Brass	B 21	1
062	Disc Seat Ring	Rubber (Buna N)	D 2000 BK 807	1
061	Body Seat Ring	Bronze	B 62	1
024	Seat Holder	Ductile Iron	A 536 Gr. 65-45-12	1
016	Weight	Cast Iron	A 126 Class B	1
023	Arm	Ductile Iron	A 536 Gr. 65-45-12	1
014	Cover	Cast Iron	A 126 Class B	1
003	Disc	Cast Iron	A 126 Class B	1
001	Body	Cast Iron	A 126 Class B	1

HYDRO SHELL	TEST PRESSURE
300 PSI.	150 PSI.
HYDRO VALVE SEAT	150 PSI.
HYDRO BACK SEAT	PSI.
AIR SEAT	PSI.
STEAM	PSI.

WORKING PRESSURE 150 PSI.

HENRY PRATT - CCNE

401 S. HIGHLAND AVE. AUBURN, IL 60508
 DR. JON COLPAN
 N.T.S. DATE 10/20/10 REF. DWG. USA1323D

PHONE: 630.844.4000; FAX: 630.844.4124

SIZE 18" SWING CHECK VALVE AWMA C508
 BRONZE BODY SEAT RING & BUNA N DISC SEAT RING
 WITH ONE LEVER AND WEIGHT

TYPE: 8001AB1LW
 DWG NO.: HP80007
 REV: