

PRATT®

a **MUELLER** brand

LVC CYLINDER OPTIONS SERIES “VE” Knife Gate Valve

FEATURES

The following are available on all “VE” series cylinders:

REPAIR KITS

Kit includes cups and seals to repair worn components. It is recommended that at least one repair kit be kept on hand for each cylinder size.

STAINLESS STEEL (SS) ROD

17-4PH stainless steel rod should be used in environments where pitting of the cylinder rod may occur. Pitting of the cylinder rod could lead to premature rod seal failure.

VITON SEALS

Used on cylinders exposed to high temperatures. Recommended on any cylinder that will reach operating temperatures of 200°F or higher.

INTERNAL PLATING

For use with water or when operating air contains moisture.



MUELLER

CYLINDER SIZING CHART

VALVE SIZE	CYLINDER PRESSURE (PSI)	MAXIMUM PRESSURE DIFFERENTIAL ACROSS GATE											
		UP TO 25 PSI		25-50 PSI		50-75 PSI		75-100 PSI		100-125 PSI		125-150 PSI	
		CYLINDER SIZE		CYLINDER SIZE		CYLINDER SIZE		CYLINDER SIZE		CYLINDER SIZE		CYLINDER SIZE	
		53, 65, 77	93	53, 65, 77	93	53, 65, 77	93	53, 65, 77	93	53, 65, 77	93	53, 65, 77	93
3	40	6	4	6	4	6	4	6	5	6	5	6	5
	60	5	3.25	5	3.25	5	3.25	5	4	5	4	5	4
	80	4	2.5	4	3.25	4	3.25	4	3.25	4	3.25	4	3.25
	100	4	2.5	4	2.5	4	2.5	4	2.5	4	2.5	4	2.5
4	40	6	4	6	5	6	5	7	5	7	6	7	6
	60	5	3.25	5	4	5	4	6	5	6	5	6	5
	80	4	2.5	4	3.25	5	4	5	4	5	4	6	4
	100	4	2.5	4	3.25	5	3.25	5	3.25	5	4	5	4
6	40	7	5	7	6	8	6	8	7	8	7	10	8
	60	6	4	6	5	7	5	7	6	7	7	8	7
	80	6	4	6	4	6	4	6	5	7	5	7	6
	100	5	3.25	5	4	6	4	6	5	6	5	7	5
8	40	8	6	8	7	8	7	10	8	12	10	12	10
	60	7	5	7	6	7	6	8	7	10	8	10	8
	80	6	4	6	5	6	5	7	6	8	7	8	7
	100	6	4	6	5	6	5	7	6	7	6	7	6
10	40	10	7	10	8	12	10	12	10	14	12	14	12
	60	8	6	8	7	8	7	10	8	12	10	12	10
	80	7	5	7	6	7	6	8	7	10	8	12	8
	100	7	5	7	6	7	6	8	7	8	7	10	8
12	40	12	8	12	10	12	10	14	12	16	14	16	14
	60	10	6	10	7	10	8	12	10	14	12	14	12
	80	8	6	8	7	10	7	10	8	12	10	12	10
	100	8	5	8	6	8	7	10	8	10	8	12	10
14	40	12	10	12	12	14	12	16	14	18	16	18	16
	60	12	7	12	10	12	10	14	12	14	12	16	14
	80	10	7	10	8	10	8	12	10	12	10	14	12
	100	8	6	8	7	10	8	10	10	12	10	12	10
16	40	14	10	14	12	16	14	18	16	20	16	20	18
	60	12	8	12	10	14	12	14	12	16	14	18	14
	80	10	7	10	8	12	10	14	12	14	12	16	14
	100	8	7	10	8	10	10	12	10	12	12	14	12
18	40	14	12	16	14	18	16	20	18	22	20	22	22
	60	12	10	14	12	14	14	16	14	18	16	18	18
	80	10	8	12	10	14	12	14	12	16	14	16	16
	100	10	8	10	10	12	10	12	12	14	12	14	14
20	40	16	12	18	16	20	18	22	20	22	22	24	24
	60	12	10	14	12	16	14	18	16	20	18	20	20
	80	10	10	12	12	14	12	16	14	16	16	18	16
	100	10	8	12	10	12	12	14	12	16	14	16	14
24	40	16	14	20	18	22	20	24	24	*	*	*	*
	60	14	12	16	14	18	18	20	20	22	20	24	22
	80	12	10	14	12	16	14	18	16	20	18	20	20
	100	12	10	12	12	14	14	16	14	18	16	18	18

* Consult Factory

675 Mitchell Avenue, Woodland, WA 98674, moreinfo@prattvalve.com, P: 800.423.1323

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Mi.Net®, Milliken®, Pratt®, Singer®, and U.S. Pipe Valve & Hydrant. Please see www.muellerwp.com/about to learn more.

Copyright © 2018 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).

