

LVC FIGURE F193 FABRICATED BONNETED Knife Gate Valve

FEATURES

- Fabricated heavy duty bonneted knife gate valves are ideally suited to reduce fugitive emissions and packing leakage.
- All stainless steel construction available.
- Wiper between body and bonnet prevents solids from entering bonnet.
- Fabricated bonnet design pressure same as valve pressure rating.
- Standard TFE lubricated synthetic packing (TLSP) rated for 500° F and a pH range of 3-11.
- Heavy duty body design resists deflection from line loads and internal pressure.
- Gate design withstands full rated pressure.
- Body cavity, seat configuration, and beveled gate design provide shut off capability in thick media such as pulp stock and slurries, or solid media like pellets and powders.
- Heavy fabricated steel yoke prevents bending or twisting under extreme loads.
- Easy conversion from gear operator to pneumatic or hydraulic cylinder, or electric motor operator using existing cast yoke.
- Hard faced seat available to prevent galling in high cycle and/or high end pressure or abrasive applications.
- V-Port or O-Ring resilient seats available to suit specific applications.
- Precision machined stainless steel gate provides superior seating capability.
- Stainless steel stem provides corrosion resistance.
- Flange drilling meets ANSI B16.47 CL150 series A standards with all tapped holes and serrated gasket faces.
- Full port ID.
- Designed in accordance with AWWA C520 Knife Gate Valves, 2" – 96".





MATERIALS OF CONSTRUCTION

MATERIALS CODE	W44 / W66	A44 / A66	A77
Body Liner, Seat & RF	304/316	304/316	317
Flanges, Ext. Trim	Steel	304/316	317
Gate	304/316	304/316	317
Packing Gland	Steel	304/316	317
Packing Bolting	304	304	304
Yoke	Steel	304/316	317
Stem & Clevis	304	304	304
Stem Nut	Bronze	Bronze	Bronze
Packing	TLSP	TLSP	TLSP

MODEL F193				
1	Gate			
2	Body			
3	Seat			
4	Wiper			
5	Bonnet			
6	Packing			
7	Bolts			
8	Gland			
9	Stem			
10	Yoke			
11	Stem Nut			

11 HW 10 н 5 0 4 ñ 0 3 2 ID RF BC 0000 TOT OD F-F "D" Drill & Tap "N" Holes

50 psi standard pressure, other pressures available upon request.

DIMENSIONS (INCHES) AND WEIGHTS, SQUARE BOTTOM

	SIZE	30	36	42	48	54	60
Face-to-Face	F-F	4-5/8	5-1/4	5-5/8	6	6-1/2	7-3/4
Flange OD	OD	38-3/4	46	53	59-1/2	66-1/4	73
Bolt Circle	BC	36	42-3/4	49-1/2	56	62-3/4	69-1/4
Flange Raised Face	RF	34	40-1/4	47	53-3/4	59-3/4	66
Inside Diameter	ID	30	35-7/8	42	47-1/4	54	60
No. of Bolt Holes	N	28	32	36	44	44	52
Hole D&T Size	D	1-1/4-7 UNC	1-1/2-6 UNC	1-1/2-6 UNC	1-1/2-6 UNC	1-3/4-5 UNC	1-3/4-5 UNC
C/L to Top-Stem Cover	H-OPN	120	145	176	205	230	262
Handwheel Dia.	H/W	BG4 W 20" HW	BG6 W 20″ HW	BG6 W 20" HW			
Weight - Ibs	WT	3650	4150	6450	9650	14860	20600
Stroke	S	28-13/16	35	40-1/2	47-1/4	53	59



MATERIALS OF CONSTRUCTION

MATERIALS CODE	W44 / W66	A44 / A66	A77
Body Liner, Seat & RF	304/316	304/316	317
Flanges, Ext. Trim	Steel	304/316	317
Gate	304/316	304/316	317
Packing Gland	Steel	304/316	317
Packing Bolting	304	304	304
Yoke	Steel	304/316	317
Stem & Clevis	304	304	304
Stem Nut	Bronze	Bronze	Bronze
Packing	TLSP	TLSP	TLSP

MODEL F193				
1	Gate			
2	Body			
3	Seat			
4	Wiper			
5	Bonnet			
6	Packing			
7	Bolts			
8	Gland			
9	Stem			
10	Yoke			
11	Stem Nut			

50 psi standard pressure, other pressures available upon request.

DIMENSIONS (INCHES) AND WEIGHTS, ROUND BOTTOM

	SIZE	30	36	42
Face-to-Face	F-F	4-5/8	5-1/4	5-5/8
Flange OD	OD	38-3/4	46	53
Bolt Circle	BC	36	42-3/4	49-1/2
Flange Raised Face	RF	34	40-1/4	47
Inside Diameter	ID	30	35-7/8	42
No. of Bolt Holes	N	28	32	36
Hole D&T Size	D	1-1/4-7 UNC	1-1/2-6 UNC	1-1/2-6 UNC
C/L to Top-Stem Cover	H-OPN	135	160	185
Handwheel Dia.	H/W	BG4 W 20" HW	BG4 W 20" HW	BG4 W 20" HW
Weight - lbs	WТ	3600	4050	6300
Stroke	S	28-13/16	35	40-1/2

675 Mitchell Avenue, Woodland, WA 98674, moreinfo@prattvalve.com, P: 800.423.1323

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Mi.Net®, Milliken®, Pratt®, Singer®, and U.S. Pipe Valve & Hydrant. Please see www.muellerwp.com/about to learn more.

Copyright © 2018 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc, its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).



